



Network

Bullet

QNO-C9083R

8MP IR Bullet Camera



Key Features

- Max. 8MP resolution
- Max. 30fps
- Color: 0.06Lux(F1.6, 1/30sec), BW: 0.006Lux(F1.6, 1/30sec, 30IRE)
- Focal length: 3.2~10.2mm motorized varifocal
- H.265, H.264, MJPEG codec supported
- Multiple streaming (up to 5 profiles)
- Day & Night (ICR), WDR (120dB)
- Micro SD/SDHC/SDXC 1 slot 256GB
- IP66, IK10
- PoE: Max 12W

QNO-C9083R

8MP IR Bullet Camera



Specifications

| Video | |
|---------------------------|---|
| Imaging Device | 1/2.8" CMOS |
| Resolution | 3840x2160, 3328x1872, 3072x1728, 2592x1944, 2688x1520, 1920x1080, 1600x1200, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240 |
| Max. Framerate | H.265/H.264: Max. 30fps/25fps(60Hz/50Hz) MJPEG: Max. 30fps(@8MP Max. 5fps) |
| Min. Illumination | Color: 0.06Lux(F1.6, 1/30sec, 30IRE) BW: 0.006Lux(F1.6, 1/30sec, 30IRE), 0Lux(IR LED on) |
| Video Out | USB: Micro USB Type B, 1280x720 for installation |
| Lens | |
| Focal Length (Zoom Ratio) | 3.2~10.2mm(3.2x) motorized varifocal |
| Max. Aperture Ratio | F1.6(Wide)~F3.1(Tele) |
| Angular Field of View | H: 104°(Wide)~31°(Tele) V: 55°(Wide)~17°(Tele) D: 124°(Wide)~35°(Tele) |
| Min. Object Distance | 1.2m (3.93ft) |
| Focus Control | Simple focus |
| Lens Type | DC auto iris(IR Corrected) |
| Pan / Tilt / Rotate | |
| Pan / Tilt / Rotate Range | 0°~360° / 0°~100° / 0°~360° |
| Operational | |
| Camera Title | Displayed up to 85 characters |
| Day & Night | Auto(ICR) |
| Backlight Compensation | BLC, WDR, SSSDR |
| Wide Dynamic Range | 120dB |
| Digital Noise Reduction | SSNR V, WiseNR II (Based on AI engine) |
| Motion Detection | 8ea, 8point polygonal zones |
| Privacy Masking | 32ea, 4point quadrangle zones |
| Gain Control | Low / Middle / High |
| White Balance | ATW / AWC / Manual / Indoor / Outdoor |
| LDC | Support |
| Electronic Shutter Speed | Minimum / Maximum / Anti flicker (1/5~1/12,000sec) |
| Video Rotation | Flip, Mirror, Hallway view(90°/270°) |

| | |
|-----------------------|---|
| Analytics | Classified object type: Person/Vehicle Attributes: Vehicle(Type:car/bus/truck/motorcycle/bicycle) Support DetectionShot Analytics events based on AI engine - Motion detection*, Object detection, Virtual line*(Crossing/Direction), Virtual area*(Loitering/Intrusion/Enter/Exit) Analytics events - Defocus detection, Tampering, Virtual area(Appear/Disappear) * Some of the video analytics only works with people and vehicle detection |
| Business Intelligence | Based on AI engine: People counting, Vehicle counting, Queue management, Heatmap |
| Alarm I/O | Input 1ea / Output 1ea |
| Alarm Triggers | Analytics, Network disconnect, Alarm input |
| Alarm Events | When alarm trigger occurred - File upload(image) : e-mail/FTP - Notification : e-mail - Recording : SD/SDHC/SDXC or NAS recording at event triggers - Alarm output - Handover(PTZ preset, Send message by HTTP/HTTPS/TCP) - Audio clip playback |
| Audio In | Selectable(mic in/line in) |
| Audio Out | Line out, Max.output level: 0.5Vrms |
| IR Viewable Length | 30m(98.42ft) |
| IR Wavelength | long-life 850 nm IR LED |

| | |
|-----------------------------------|--|
| Network | |
| Ethernet | RJ-45(10/100BASE-T) |
| Video Compression | H.265/H.264: Main/High, MJPEG |
| Audio Compression | G.711 u-law /G.726 Selectable G.726(ADPCM) 8KHz, G.711 8KHz G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC: 48Kbps at 16KHz |
| Smart Codec | Manual(5ea area), WiseStreamIII(Based on AI engine) |
| Bitrate Control | H.264/H.265: CBR or VBR MJPEG: VBR |
| Streaming | Unicast(20 users) / Multicast Multiple streaming(Up to 5 profiles) |
| Protocol | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP (TCP, UDP Unicast) |
| Application Programming Interface | ONVIF Profile S/G/T/M SUNAPI(HTTP API) |

| | |
|------------------------|---|
| Security | |
| OS / Firmware Protect | Secure boot, Signed firmware, Firmware encryption |
| User authentication | Digest Authentication, Prevent brute-force attack |
| Network authentication | 802.1X Authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2) |
| Secure Communication | HTTPS, SRTP, WSS(Websocket secure) |
| Access Control | Access control based on IP address |
| Data Protect | Authentication information encryption, ZIP compression encryption |
| Audit | User Access/System/Event log management |
| Device ID | Device Certificate(Hanwha Private Root CA) |
| Secure Storage | SDcard partition encrypt |
| Security Certificate | Secure by default |

| | |
|------------------|--|
| General | |
| Webpage Language | English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek |

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com

Hanwha Vision is formerly known as Hanwha Techwin.

QNO-C9083R

| | |
|--------------|--------------------------------|
| Edge Storage | Micro SD/SDHC/SDXC 1slot 256GB |
| Memory | 2GB RAM, 1GB Flash |

Environmental & Electrical

| | |
|----------------------------------|--|
| Operating Temperature / Humidity | -30°C~+55°C(-22°F~+131°F) / 0~95% RH(non-condensing) * Start up should be done at above -30°C Humidity control /w Air vent |
| Storage Temperature / Humidity | -50°C~+60°C(-58°F~+140°F) / 0~95% RH |
| Certification | IP66, IK10 |
| Input Voltage | PoE(IEEE802.3af, Class3) |
| Power Consumption | PoE: Max 12W, typical 5.3W |

Mechanical

| | |
|-----------------------------------|---|
| Color / Material | White / Aluminum |
| RAL Code | RAL9003 |
| Product Dimensions / Weight | ø93.4x245.8mm(ø3.68x9.68"), 930g(2.05 lb) |
| Compatible Conduit hole / Gangbox | Conduit hole : None Gangbox (SBO-090GP) : Single, Double, 4" Octagon (sold separately) |
| Backbox | SBO-140BW |

Certifications & Standards

| | |
|-------------|--|
| EMC | FCC 47 CFR 15 Subpart B Class A ICES-3(A)/NMB-3(A) CE/UKCA - EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3 VCCI CISPR 32 Class A RCM AS/NZS CISPR 32 Class A |
| Safety | UL 62368-1, CAN/CSA C22.2 NO. 62368-1 IEC/EN 62471 |
| Environment | IEC/EN 63000 IEC/EN 60529 IP66, IEC/EN 62262 IK10 |

DORI (EN62676-4 standard)

| | |
|---------------------------|--|
| Detect (25PPM/ 8PPF) | Wide: 60.0m(196.86ft) / Tele: 276.9m(908.57ft) |
| Observe (63PPM/ 19PPF) | Wide: 24.2m(78.74ft) / Tele: 111.7m(363.43ft) |
| Recognize (125PPM/ 38PPF) | Wide: 12.0m(39.37ft) / Tele: 55.4m(181.71ft) |
| Identify (250PPM/ 76PPF) | Wide: 6.0m(19.69ft) / Tele: 27.7m(90.86ft) |

QNO-C9083R

8MP IR Bullet Camera



CAD

Unit:mm [inch]

