

XNV-6081

2MP Network Dome Camera




Key Features

- Max. 2Megapixel resolution
- 0.015Lux@F1.4 (Color), 0.0015Lux@F1.4 (B/W)
- Day & Night (ICR), WDR (150dB)
- Hallway View, WiseStreamII Support
- Video & audio analytics, Audio playback
- DIS and shock detection with built-in gyro sensor
- Modular structure, PoE, 12VDC, 24VAC (Optional)
- IP66/IP67, IK10+, NEMA4X, PoE, 12VDC

Dimensions

Unit : mm (inch)




Accessories (Optional)



SBP-187HMW /
SBP-187HM



SBC-180B



SPC-100AC

XNV-6081

| VIDEO | |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Imaging Device | 1/2.8" 2MP CMOS |
| Effective Pixels | 1945(H) x 1097(V) |
| Min. Illumination | Color : 0.015Lux (F1.4, 1./30sec) / B/W : 0.0015Lux (F1.4, 1/30sec) |
| Video Out | CVBS : 1.0Vp-p / 75Ω composite, 720 x 480(N), 720 x 576(P) for installation USB : Micro USB Type B, 1280 x 720 for installation |
| LENS | |
| Focal Length (Zoom Ratio) | 2.8~12mm (4.3x) motorized varifocal |
| Max. Aperture Ratio | F1.4(Wide) ~ F3.6(Tele) |
| Angular Field of View | H : 119.5°(Wide)~27.9°(Tele) / V : 62.8°(Wide)~15.7°(Tele) / D : 142.1°(Wide)~32.0°(Tele) |
| Min. Object Distance | 0.5m (1.64ft) |
| Focus Control | Simple focus |
| Lens Type | DC auto iris, P iris |
| PAN / TILT / ROTATE | |
| Pan / Tilt / Rotate Range | 0°~360° / -45°~85° / 0°~355° |
| OPERATIONAL | |
| Camera Title | Displayed up to 85 characters |
| Day & Night | Auto (ICR) |
| Backlight Compensation | BLC, HLC, WDR, SSSR |
| Wide Dynamic Range | 150dB |
| Digital Noise Reduction | SSNR V |
| Digital Image Stabilization | Support (built-in gyro sensor) |
| Defog | Support |
| Motion Detection | 8ea, 8point polygonal zones |
| Privacy Masking | 32ea, polygonal zones - Color : Grey / Green / Red / Blue / Black / White - Mosaic |
| Gain Control | Low / Middle / High |
| White Balance | ATW / AWC / Manual / Indoor / Outdoor |
| LDC | Support |
| Electronic Shutter Speed | Minimum / Maximum / Anti flicker (2~1/12,000sec) |
| Digital PTZ | Support (Preset, Group) |
| Video Rotation | Flip, Mirror, Hallway view (90°/270°) |
| Analytics | Defocus detection, Directional detection, Fog detection, Face detection, Motion detection, Digital auto tracking, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Sound classification, Shock detection |
| Business Intelligence | People counting, Queue management, Heatmap |
| Alarm I / O | Input 1ea / Output 1ea |
| Alarm Triggers | Analytics, Network disconnect, Alarm input |
| Alarm Events | File upload via FTP and e-mail Notification via e-mail SD/SDHC/SDXC or NAS recording at event triggers Alarm output Handover Audio playback |
| Audio In | Selectable (mic in/line in), Supply voltage : 2.5VDC (4mA), Input impedance : 2K Ohm |
| Audio Out | Line out, Max. output level : 1Vrms |
| NETWORK | |
| Ethernet | RJ-45 (10/100BASE-T) |
| Video Compression | H.265/H.264 : Main / Baseline / High, MJPEG |
| Resolution | 1920 x 1080, 1280 x 1024, 1280 x 960, 1280 x 720, 1024 x 768, 800 x 600, 800 x 448, 720 x 576, 720 x 480, 640 x 480, 640 x 360, 320 x 240 |

XNV-6081

| | |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Max. Framerate | H.265/H.264 : Max. 60fps / 50fps (60Hz/50Hz) MJPEG : Max. 30fps / 25fps (60Hz/50Hz) |
| Smart Codec | Manual (Sea area), WiseStream II |
| Video Quality Adjustment | H.264/H.265 : Target bitrate level control MJPEG : Target bitrate level control |
| Bitrate Control | H.264/H.265 : CBR or VBR MJPEG : VBR |
| Streaming | Unicast (20 users) / Multicast Multiple streaming (Up to 10 profiles) |
| Audio Compression | G.711 u-law / G.726 Selectable G.726 (ADPCM) 8KHz, G.711 8KHz G.726 : 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC : 48Kbps at 16KHz |
| Protocol | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP |
| Security | HTTPS (SSL) login authentication Digest login authentication IP address filtering User access log 802.1X authentication (EAP-TLS, EAP-LEAP) |
| Edge Storage | Micro SD/SDHC/SDXC 2slot 512GB |
| Application Programming Interface | ONVIF Profile S/G SUNAPI (HTTP API) Wisenet open platform |
| Webpage Language | English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek |
| Web Viewer | Supported OS : Windows 7, 8.1, 10, Mac OS X 10.10, 10.11, 10.12 Recommended Browser : Google Chrome Supported Browser : MS Explorer11, MS Edge, Mozilla Firefox(Windows 64bit only), Apple Safari (Mac OS X only) |
| Memory | 1024MB RAM, 256MB Flash |
| ENVIRONMENTAL | |
| Operating Temperature / Humidity | -50°C ~ +60°C (-58°F ~ +140°F) / Less than 90% RH * Start up should be done at above -35°C |
| Storage Temperature / Humidity | -50°C ~ +60°C (-58°F ~ +140°F) / Less than 90% RH |
| Certification | IP66/IP67, IK10+, NEMA4X |
| ELECTRICAL | |
| Input Voltage | PoE (IEEE802.3af, Class3), 24VAC (Optional), 12VDC |
| Power Consumption | PoE : Max 7.0W, typical 4.9W 12VDC : Max 5.4W, typical 3.7W 24VAC : Max 7.1W, typical 4.9W |
| MECHANICAL | |
| Color / Material | White / Aluminum |
| RAL Code | RAL9003 |
| Product dimensions / weight | Ø180x125mm(7.09x4.92"), 1.75Kg(3.86 lb) |
| Conduit hole | 3/4" |
| Hanging mount (Dome) | SBP-187HMW, SBP-187HM |
| Skin cover (Dome) | SBC-180B |
| Power module | SPC-100AC |

* The latest product information / specification can be found at hanwha-security.com

* Design and specifications are subject to change without notice.

* Wisenet is the proprietary brand of **Hanwha Techwin**.