

IP senzory HW group



	STE2	Poseidon2 3266	Poseidon2 3268	Poseidon2 3468	Poseidon2 4002	HWg-Ares 10	HWg-Ares 12	Damocles2 Mini	Damocles2 1208	Damocles2 2404i	HWg-PWR 3 HWg-PWR 12 HWg-PWR 25	HWg-SMS GW	HWg-WLD	HWg-WLD Relay	IP WatchDog2 Lite
LAN (Ethernet)	•	•	•	•	•				•	•	•	•	•		•
WiFi															
GSM/GPRS data						•	•								
PoE								• (volitelně)	• (volitelně)	•				• (volitelně)	
1-Wire senzory	3	8	8	8	16	3	14								
1-Wire UNI senzory		•	•	•	•	•	•								
Digitální vstupy	2	4	4	4	12	2	2	4	12	24	8 (detekce fáze)				
Digitální výstupy			2 (relé)	2 (relé 230 V)	4 (relé)			2 (relé)	8 (OC)	4 (relé)				1 (relé)	2 (relé)
M-BUS měřiče											3 / 12 / 25				
Rozhraní IP WEB	•	•	•	•	•			•	•	•	•	•	•		•
Odesílání SMS samotným modulem						•	•					•			
Podpora externí SMS gateway	•	•	•	•	•			•	•	•	•			•	•
E-mail	•	•	•	•	•	•	•	•	•	•	•			•	•
SNMP	•	•	•	•	•	•	•	•	•	•	•			•	•
SNMP Trap		•	•	•	•	•	•	•	•	•	•			•	•
HWg-Push (podpora SensDesk.com)	•	•	•	•	•	•	•	•	•	•	•			•	•
Modbus/TCP		•	•	•	•			•	•	•	•				
Logování hodnot		250.000 záz.n.	250.000 záz.n.	250.000 záz.n.	250.000 záz.n.	170.000 záz.n.	170.000 záz.n.	•	•	•	170.000 záz.n.	fronta 100 SMS			200 záz.n.
Napájení	5 V _{SS}	9-30 V _{SS}	9-30 V _{SS}	9-30 V _{SS} / -48 V _{SS}	9-30 V _{SS}	9-30 V _{SS}	9-30 V _{SS}	9-30 V _{SS}	9-30 V _{SS}	9-30 V _{SS} / -48 V _{SS}	230 V _{1R}	9-30 V _{SS}	5 V _{SS}	12 V _{SS} / z 1-Wire rozhr.	9-30 V _{SS}

- Standardní funkce
- Lze aktivovat / nastavit tuto funkci

