

FULL HD PRO-GRADE LED COLOUR MONITOR

WBXML20



This professional grade widescreen LED 19.53" colour monitor offers HDMI, VGA, & BNC inputs. With an additional BNC looping output its versatility will allow it to work for any application. Boasting 16.7 million colours & FHD Resolution this monitor will make your video come to life.

- 19.53" Diagonal Viewing Size
- 1920x1080P Full HD Resolution
- VGA, BNC & HDMI Inputs
- 24/7 Operation
- IPS Technology, 178° Viewing Angle
- Source Auto Detection
- Quick Touch Scalability 16:9/4:3
- Includes Audio, VGA & Dual Power Cables (EU,UK)
- 36 Months Warranty

PART #: WBXML20

UPC : 811914029830

LENGTH:

18.52inch/470.4mm WIDTH :

5.87inch/149.1mm HEIGHT :

13.43inch/341.2mm

WEIGHT : 8.8lbs/4kg

SPEC SHEET

Model	WBXML20
Screen Diagonal Dimension(inches)	19.53
Viewable Area WxH (inches/mm)	17.12inch*9.4inch / 435mm*238.8mm
Led Type	LED
Pixel Pitch (mm)	0.2265 x 0.221
Screen Maximum Resolution	1920x1080
Display Resolutions	640 x 480; 800 x 600; 1024 x 768; 1280 x 1024; 1366 x 768; 1920 x 1080
Supported Input Resolutions	640 x 480; 800 x 600; 1024 x 768; 1280 x 1024; 1366 x 768; 1920 x 1080
Refresh Rate (Hz)	60
Color Depth (M)	16.7
Brightness (cd/ m ²)	250
Auto Adjust	Yes
Monitor Aspect Ratio	16:9
Display Aspect Ratio	OSD selectable 16:9 or 4:3
Horizontal TV Lines	1080
Contrast Ratio	1000 :1SCR
Response Time (ms)	5(GTG)
View Angle H/V (degrees)	178°x 178°/CR > 10
Digital Video Inputs	HDMI up to 1920 x1080
Analog Video In/Out	VGA up to 1920x1080, BNC CVBS looping
Audio Inputs (stereo)	1x3.5mm mini-jack
Speakers (W)	2 x 3
Stand-by (W)	<0.5
Power Consumption (W)	19W Typical
Monitor Body Dimensions (inches/mm)	18.52inchx11.1inchx1.88inch / 470.4mmx282mmx47.7mm
Dimensions Monitor+Stand (inches/mm)	18.52inchx13.43inchx5.87inch/ 470.4mmx341.2mmx149.1mm
Panel Surface	Matte black
Case & Stand Material	Plastic
VESA Mounting Pattern (mm)	100 x 100
Base/Stand Included	Yes
Base Tilt Angle	-5°~15°
Weight Cabinet Only (lb/kg)	5.8lbs / 2.6kg
Weight Cabinet+Base Stand(lb/kg)	6.3lbs / 2.85kg
Power Supply (internal)	AC 100-240V~50/60Hz 1.1A
Operating Temperature	0°C~40°C / 32°F~104°F
Storage Temperature	-20°C~50°C / -4°F~122°F
Operating Humidity	10~90%
Accessories	Dual Power cable (EU,UK)/VGA cable/Audio cable/IR Remote/Batteries Hinge cover/Screws/Base of stand/Stand support/User manuals
Rack Mount Screw Size (mm)	Screws for Mounting Monitor, Screws Type: PMΦ4.0x6mm/4pcs/ PMΦ4.0x8mm/4pcs Screws for Securing Base of Stand, Screws Type: BBΦ4.0x7mm/5pcs Screws for Installing Monitor Stand, Screws Type: BMΦ4.0x8mm/2pcs
Certifications	CE/FCC/ROHS/HDMI/UL/WEEE/REACH
Warranty	36 Months